



a vinmar company



# Alfaten 200

## Product Description

Recycled LDPE from greenhouse natural covering film scrap.

Features: 100% Recyclate content. Natural color.

## Applications

Construction, industrial & silage films, bags, hoods & sacks, injection moulding, irrigation pipes, corrugated tubing.

| Properties          | Method            | Unit                | Value               |
|---------------------|-------------------|---------------------|---------------------|
| MFR (190°C, 2,16kg) | UNE EN ISO 1133   | g / 10min           | 0,2 – 0,5           |
| Density             | UNE EN ISO 1183-1 | g / cm <sup>3</sup> | 0,90 – 0,92         |
| Moisture            | EN 12099          | %                   | 0,06                |
| Polymer Content     | UNE EN ISO 3451-1 | %                   | 97                  |
| Filtration          | Mesh Size         | µm                  | 120                 |
| Particle Shape      | Visual Inspection |                     | Lentil-shape Pellet |

All data information herein refers to typical values. Since conditions of product use is outside our control, we make no warranties and assume no liability in connection with any use of this information.

Parque Industrial de Alhama.  
C/Alemania sn.  
30840, Alhama de Murcia, Spain.  
Tel: (+34) 968 63 22 21  
www.gwcplastics.com



RecyClass

