

Green World Compounding
 Parque Industrial de Alhama
 C/ Alemania, s/n
 30840 Alhama de Murcia
 Murcia (España)
 Tel: (+34) 968 63 22 21
 Fax: (+34) 968 63 22 33
 salvador.navarro@gwplastics-group.com
 www.gwplastics-group.com

Alfaten 2000 Natural

Description

- Recycled low-density polyethylene (LDPE) in pellet form
- Suitable for extrusion and injection process
- Source:
 - Linear low-density polyethylene (LLDPE) natural mulch film and LDPE natural agricultural film
- Applications:
 - agricultural, construction, industrial & silage films, bags, hoods & sacks, injection moulding, irrigation pipes, corrugated tubing,...

Properties

	Method	Unit	Value Range
Density	UNE EN ISO 1183	g / cm ³	0,92 – 0,95
MFI (190°C, 2'16kg)	UNE EN ISO 1133	g / 10min	0,3 – 0,5
Tensile Strain at Break	ISO 521	MPa	> 15
Elongation at break	ISO 521	%	> 450
Humidity	ISO 787/2	%	≤ 0,1
Ash content	ISO 3451-1, A	%	< 3
Color	Visual inspection	NA	Light brown

This information is offered in good faith and meant only as a guide. The transformer should take into account that it is a recycled material and subjected to some variations in their properties. Therefore, he is responsible for the processing conditions and the final use of the product.

Rev. Std
 Date 18-08-2020
 SNN

