



a vinmar company



Verdant LDA410C

Product Description

Multimodal HDPE-highly enhanced recycled LDPE. This product contains also a circular economy enhancer package that offsets brownish shade of recycled polyethylene and minimizes gel formation. 90% Recycled content. Natural color.

Applications

Heavy duty sacks (HDSS), bags, Liners, Protective films, Collation Shrink, and other high performance films.

Properties	Method		Unit	Nominal Value
MFR (190°C, 2,16kg)	UNE EN ISO 1133		g / 10min	0,2 – 0,7
Density	UNE EN ISO 1183-1		g / cm ³	0,94 – 0,95
Moisture	EN 12099		%	0,06
Polymer Content	UNE EN ISO 3451-1		%	97
Filtration	Mesh Size		µm	90
Particle Shape	Visual Inspection			Lentil-shape Pellet
Tensile Strength, Break	UNE EN ISO 527-1	MD	MPa	16
		TD	MPa	17
Tensile Elongation, Break	UNE EN ISO 527-3	MD	%	415
		TD	%	430
Elmendorf Tear Strength	UNE EN ISO 6383-2	MD	N	2,2
		TD	N	3,7
Dart Drop Impact Strength	UNE EN ISO 7765-1		g	129

The technical information on film properties is based on blown film 33µm thickness and all data information herein refers to typical values. Since conditions of product use is outside our control, we make no warranties and assume no liability in connection with any use of this information.

Parque Industrial de Alhama.
C/Alemania sn.
30840, Alhama de Murcia, Spain.
Tel: (+34) 968 63 22 21
www.gwcplastics.com



RecyClass

